


## PN AOS 90

### Lisované hrdlo 90°

Těsnící hlava s O-kroužkem metrická, těžká konstrukční řada (DKOS), 90° úhlová armatura  
Materiál: Ocel-pozink-chromátovaná na žluto  
Skupina výrobků 1122



Označení	DN	Velikost	Palec	Závit	Trubka-0	SW	O-kroužek	T
PN 04 AOS 90	5	3	3/16"	M 16x1,5	8	19	6x1,5	14,05
PN 06 AOS 03 90	6	4	1/4"	M 14x1,5	6	17	4x1,5	12,05
PN 06 AOS 04 90	6	4	1/4"	M 16x1,5	8	19	6x1,5	14,05
PN 06 AOS 90	6	4	1/4"	M 18x1,5	10	22	7,5x1,5	16,05
PN 06 AOS 08 90	6	4	1/4"	M 20x1,5	12	24	9x1,5	18,05
PN 08 AOS 06 90	8	5	5/16"	M 18x1,5	10	22	7,5x1,5	16,05
PN 08 AOS 90	8	5	5/16"	M 20x1,5	12	24	9x1,5	18,05
PN 10 AOS 06 90	10	6	3/8"	M 18x1,5	10	22	7,5x1,5	16,05
PN 10 AOS 08 90	10	6	3/8"	M 20x1,5	12	24	9x1,5	18,05
PN 10 AOS 90	10	6	3/8"	M 22x1,5	14	27	10x2	20,05
PN 10 AOS 13 90	10	6	3/8"	M 24x1,5	16	30	12x2	22,05
PN 13 AOS 90	12	8	1/2"	M 24x1,5	16	30	12x2	22,05
PN 16 AOS 13 90	16	10	5/8"	M 24x1,5	16	30	12x2	22,05
PN 16 AOS 90	16	10	5/8"	M 30x2	20	36	16,3x2,4	27,40
PN 16 AOS 90 L 100	16	10	5/8"	M 30x2	20	36	16,3x2,4	27,40
PN 20 AOS 16 90	20	12	3/4"	M 30x2	20	36	16,3x2,4	27,40
PN 20 AOS 90	20	12	3/4"	M 36x2	25	46	20,3x2,4	33,40
PN 25 AOS 20 90	25	16	1"	M 36x2	25	46	20,3x2,4	33,40
PN 25 AOS 90	25	16	1"	M 42x2	30	50	25,3x2,4	39,40
PN 32 AOS 25 90	32	20	1"1/4	M 42x2	30	50	25,3x2,4	39,40
PN 32 AOS 90	32	20	1"1/4	M 52x2	38	60	33,3x2,4	45,40